

SMUA60 SERIES

63W U-Bracket Power Supply for Medical Equipment



- Wide Input Voltage 90 to 264 VAC, 47 to 63 Hz
- Single to Quad Output
- Input Surge Current, Over Voltage, Over Load and Output Voltage Protection
- Power Fail Detect (Optional)
- Class I Insulation
- All units are 100% burned in and tested

5 Year Warranty

Approvals:

Single Output				
Part Number	Output Voltage	Max. Output Current	Total Regulation	Max. Output Power
SMUA60-S01	3 - 5 VDC	16.6 - 10.0 A	5%	50W
SMUA60-S02	5 - 6 VDC	11.0 - 9.16 A	5%	55W
SMUA60-S03	6 - 8 VDC	10.0 - 7.50 A	5%	60W
SMUA60-S04	8 - 11 VDC	7.87 - 5.72 A	3%	63W
SMUA60-S05	11 - 13 VDC	5.72 - 4.84 A	3%	63W
SMUA60-S05-1	11 - 13 VDC	4.09 - 3.46 A	3%	45W
SMUA60-S06	13 - 16 VDC	4.84 - 3.93 A	3%	63W
SMUA60-S07	16 - 21 VDC	3.93 - 3.00 A	3%	63W
SMUA60-S08	21 - 27 VDC	3.00 - 2.33 A	2%	63W
SMUA60-S09	27 - 33 VDC	2.33 - 1.90 A	2%	63W
SMUA60-S10	33 - 40 VDC	1.90 - 1.57 A	2%	63W

Multi Output																	
Part Number	Output 1				Output 2				Output 3				Output 4				Max. Output Power
	Vonom	lomin	lomax	Regmax	Vonom	lomin	lomax	Regmax	Vonom	lomin	lomax	Regmax	Vonom	lomin	lomax	Regmax	
SMUA60-D00	+3.3V	1.4A	7A	7%	+12V	0.6A	3A	5%									59.1W
SMUA60-D01	+5V	0.7A	7A	5%	+12V	0.3A	3A	5%									63W
SMUA60-D02	+5V	0.7A	7A	5%	+15V	0.3A	3A	5%									63W
SMUA60-D03	+5V	0.7A	7A	5%	+24V	0.4A	2A	5%									63W
SMUA60-D04	+3.3V	1.4A	7A	7%	+5V	0.5A	5A	5%									48.1W
SMUA60-D15	+5V	0.7A	7A	5%					-24V	0.2A	2A	5%					63W
SMUA60-T00	+3.3V	1.2A	6A	7%	+12V	0.6A	3A	5%	-12V	0A	0.8A	5%					63W
SMUA60-T00-1	+3.3V	1.2A	6A	7%	+12V	0.6A	3A	5%	+12V	0A	0.8A	5%					63W
SMUA60-T01	+5V	0.6A	6A	5%	+12V	0.3A	3A	5%	-5V	0A	0.8A	5%					63W
SMUA60-T01-1	+5V	0.6A	6A	5%	+12V	0.3A	3A	5%	+5V	0A	0.8A	5%					63W
SMUA60-T02	+5V	0.6A	6A	5%	+12V	0.6A	3A	5%	-12V	0A	0.8A	5%					63W
SMUA60-T02-1	+5V	0.6A	6A	5%	+12V	0.6A	3A	5%	+12V	0A	0.8A	5%					63W
SMUA60-T03	+5V	0.6A	6A	5%	+15V	0.3A	3A	5%	-15V	0A	0.8A	5%					63W
SMUA60-T03-1	+5V	0.6A	6A	5%	+15V	0.3A	3A	5%	+15V	0A	0.8A	5%					63W
SMUA60-T05	+5V	1.2A	6A	5%	+24V	0.4A	2A	5%	-12V	0A	0.8A	5%					63W
SMUA60-T05-1	+5V	1.2A	6A	5%	+24V	0.4A	2A	5%	+12V	0A	0.8A	5%					63W
SMUA60-T06	+3.3V	1.2A	6A	7%	+12V	0.6A	3A	5%	-5V	0A	0.8A	5%					59.8W
SMUA60-T06-1	+3.3V	1.2A	6A	7%	+12V	0.6A	3A	5%	+5V	0A	0.8A	5%					59.8W
SMUA60-T08	+3.3V	0.5A	5A	7%	+5V	0.5A	5A	5%	-12V	0A	1A	5%					53.5W
SMUA60-T08-1	+3.3V	0.5A	5A	7%	+5V	0.5A	5A	5%	+12V	0A	1A	5%					53.5W
SMUA60-Q00	+3.3V	1.2A	6A	7%	+12V	0.6A	3A	5%	-12V	0A	0.8A	5%	-5V	0A	0.8A	5%	63W
SMUA60-Q00-1	+3.3V	1.2A	6A	7%	+12V	0.6A	3A	5%	-12V	0A	0.8A	5%	+5V	0A	0.8A	5%	63W
SMUA60-Q00-2	+3.3V	1.2A	6A	7%	+12V	0.6A	3A	5%	+12V	0A	0.8A	5%	-5V	0A	0.8A	5%	63W
SMUA60-Q00-3	+3.3V	1.2A	6A	7%	+12V	0.6A	3A	5%	+12V	0A	0.8A	5%	+5V	0A	0.8A	5%	63W
SMUA60-Q01	+5V	0.6A	6A	5%	+12V	0.3A	3A	5%	-12V	0A	0.8A	5%	-5V	0A	0.8A	5%	63W
SMUA60-Q01-1	+5V	0.6A	6A	5%	+12V	0.3A	3A	5%	-12V	0A	0.8A	5%	+5V	0A	0.8A	5%	63W
SMUA60-Q01-2	+5V	0.6A	6A	5%	+12V	0.3A	3A	5%	+12V	0A	0.8A	5%	-5V	0A	0.8A	5%	63W
SMUA60-Q01-3	+5V	0.6A	6A	5%	+12V	0.3A	3A	5%	+12V	0A	0.8A	5%	+5V	0A	0.8A	5%	63W
SMUA60-Q02	+5V	1.2A	6A	5%	+12V	0.6A	3A	5%	-12V	0A	0.8A	5%	-12V	0A	0.8A	5%	63W
SMUA60-Q02-1	+5V	1.2A	6A	5%	+12V	0.6A	3A	5%	-12V	0A	0.8A	5%	+12V	0A	0.8A	5%	63W
SMUA60-Q02-2	+5V	1.2A	6A	5%	+12V	0.6A	3A	5%	+12V	0A	0.8A	5%	-12V	0A	0.8A	5%	63W
SMUA60-Q02-3	+5V	1.2A	6A	5%	+12V	0.6A	3A	5%	+12V	0A	0.8A	5%	+12V	0A	0.8A	5%	63W
SMUA60-Q03	+5V	1.2A	6A	5%	+12V	0.6A	3A	5%	-12V	0A	0.8A	5%	-24V	0A	0.8A	5%	63W
SMUA60-Q03-1	+5V	1.2A	6A	5%	+12V	0.6A	3A	5%	-12V	0A	0.8A	5%	+24V	0A	0.8A	5%	63W
SMUA60-Q03-2	+5V	1.2A	6A	5%	+12V	0.6A	3A	5%	+12V	0A	0.8A	5%	-24V	0A	0.8A	5%	63W
SMUA60-Q03-3	+5V	1.2A	6A	5%	+12V	0.6A	3A	5%	+12V	0A	0.8A	5%	+24V	0A	0.8A	5%	63W
SMUA60-Q04	+5V	0.6A	6A	5%	+15V	0.3A	3A	5%	-15V	0A	0.8A	5%	-5V	0A	0.8A	5%	63W
SMUA60-Q04-1	+5V	0.6A	6A	5%	+15V	0.3A	3A	5%	-15V	0A	0.8A	5%	+5V	0A	0.8A	5%	63W
SMUA60-Q04-2	+5V	0.6A	6A	5%	+15V	0.3A	3A	5%	+15V	0A	0.8A	5%	-5V	0A	0.8A	5%	63W
SMUA60-Q04-3	+5V	0.6A	6A	5%	+15V	0.3A	3A	5%	+15V	0A	0.8A	5%	+5V	0A	0.8A	5%	63W

Electrical Characteristics					
Parameter	Test Conditions	Min.	Typ.	Max.	Unit
Input Voltage	Operating Voltage	90		264	VAC
Input Frequency		47		63	Hz
Output Power Range	Vin=90 to 264 VAC	0		63	W
Input Current (Low Line)	Io=Full load, Vin=115VAC			1.6	A
Input Current (High Line)	Io=Full load, Vin=230VAC			0.8	A
Low Line Inrush Current	Io=Full load, 25°C, Cool start, Vin=115VAC		15	18	A
High Line Inrush Current	Io=Full load, 25°C, Cool start, Vin=230VAC		21	25	A
Efficiency	Io=Full load, Vin=230VAC	70	80	85	%
Line Regulation	Io=Full load		0.5	1	%
Load Regulation	Vin=230VAC		3	7	%
Over Voltage Protection		112		132	%
Over Current Protection		110		150	%
Transient Response	Io=Full load to Half Load, Vin=100VAC			4	mS
Hold-Up Time	Io=Full load, Vin=110VAC	16			mS
Start Up Time	Io=Full load, Vin=100VAC	0.3	1	2	S
* Ripple & Noise (Peak to Peak)	Full load, Vin=90VAC		0.5	1	%
Safety Ground Leakage Current	Io=Full load, Vin=240VAC		0.1	0.3	mA
Temperature Coefficient	All output	-0.04		0.04	%/°C


* Note: The Ripple & Noise which is under 3.3VDC at 2% max

Conditions					
Parameter	Test Conditions	Min.	Typ.	Max.	Unit
Operating Temperature		0		70	°C
Storage Temperature		-40		85	°C
Relative Humidity		5		95	%
Operating Temperature at 25°C, Calculated per MIL-HDBK-217F		0.1			M Hrs

De-rate linearly from 100% load at 50°C to 50% load at 70°C

Approvals and Compliance			
Parameter	Test Conditions	Min.	Unit
Dielectric Withstanding Voltage for Primary to secondary	Primary to secondary	5600	VDC
Dielectric Withstanding Voltage for Primary to Ground	Primary to ground	2800	VDC
Isolation Resistance	Test Voltage = 2100VDC	50	MΩ
EMI requirements for CISPR-11	Vin=220VAC	B	CLASS
EMI requirements for FCC PART-18	Vin=110VAC	B	CLASS
Safety UL/c-UL, TUV/T-mark, CE	UL 60601-1, EN 60601-1, IEC 60601-1	n/a	n/a

Mechanical and PIN out



PIN CHART

MODEL	PIN	1	2	3	4	5	6	7	8 (Optional)
SMUA60-SXX	OUT	OUT	OUT	RTN	RTN	RTN	RTN		PFD
SMUA60-DXX	Vo2	Vo1	Vo1	COM	COM	N/C	N/C		PFD
SMUA60-D15	N/C	Vo1	Vo1	COM	COM	Vo3	N/C		PFD
SMUA60-TXX	Vo2	Vo1	Vo1	COM	COM	Vo3	N/C		PFD
SMUA60-QXX	Vo2	Vo1	Vo1	COM	COM	Vo3	Vo4		PFD

Note: Vo1: Output#1 Vo2:Output#2 Vo3:Output#3 Vo4:Output#4

Note:

- Dimensions are shown in mm.
- Weight: 425g approx.
- Input connector mates with Molex housing 09-50-3051 and Molex 2478 series crimp terminal.
- Output connector mates with Molex housing 09-50-3081 and Molex 2478 series crimp